# VARNALUX

LED SOLAR FLOODLIGHT
## REF 905465, 905466, 905467

INSTALLATION INSTRUCTIONS

1. Connect the floodlight to the waterproof line of the solar panel, and the solar panel faces the sun.

2. Install on the fixed surface

3. Can be rotated to adjust the angle

REMOTE CONTROL INSTRUCTIONS

Reserved key (invalid)

Turn On — ON | OFF — Turn Off

100% Brightness

Reserved key (invalid) — + M - — Reserved key (invalid)

50% Brightness

Light control mode — AUTO

3 hour mode — 3H | 5H — 3 hour mode

8 hour mode — 8H

Automatic light control mode:
Connect the flood light to the solar panel, press the [AUTO] button to automatically turn on or off with a daylight sensor (the button has a memory mode, only need to be set once).

Pedestal installation

Wall installation

Ceiling installation

N

N

N

35°

10°

60°

S

S

S

100% Charge efficiency

75% Charge efficiency

60% Charge efficiency

Tips:
1. The required direction is toward the southwest and forms the best installation angle with the horizontal plane. Due to the different latitudes of each region, please refer to the local best installation guide.
2. Please ensure that the solar panel is installed in a sunny area, and avoid shade from buildings or trees to ensure the longest exposure time