




DATA SHEET



LED BACK-LIT PANEL

60X60 PREMIUM 36W | DIMMABLE




AVAILABLE MODELS TRIAC DIMMABLE

Color Temp	REF No
3000K	905949
4000K	905950
6000K	905951

AVAILABLE MODELS 1-10V DIMMABLE

Color Temp	REF No
3000K	907107
4000K	907026
6000K	907108



DATA SHEET



LED BACK-LIT PANEL

60X60 PREMIUM 36W | DIMMABLE

ELECTRICAL DATA	
Wattage (Consumption)	36W
Voltage	200-240V
Max. Current	0.3 A
Operating Voltage	DC36V
Constant Current	0.90 A
Power Factor	≥0,95

PHOTOMETRICAL DATA	
Temperature (Kelvin)	3000K, 4000K or 6000K
Light color	Warm white, neutral white or cool white
Luminous efficiency	110 lm/W
Lumen	3960
Beam angle	120°
Color Rendering Index (CRI)	≥0,80
Operating Temperature	-20 °C to +50 °C
Storage Temperature	-30 °C to +60 °C
Working Humidity	10-80% RH
Humidity Storage	10-90% RH

CAPABILITIES	
Housing material	Aluminium
Housing color	White
Flicker-free	Yes
Dimmable	TRIAC or 1-10V dimmable

LIFESPAN & WARRANTY	
Lifespan	50.000 hrs
Warranty	5 years

DIMENSIONS & PACKAGING	
Product Dimensions	595x595x35 mm
Packing Dimensions	645x95x645 mm
Inner box	2 pieces
Outer box	8 pieces

ADDITIONAL INFORMATION	
IP Rating	IP41
LED Chip type	SMD2835
Luminaires Class	Class III
Certificates	CE & ROHS

AVAILABLE MODELS TRIAC DIMMABLE	
Color Temp	REF No
3000K	905949
4000K	905950
6000K	905951

AVAILABLE MODELS 1-10V DIMMABLE	
Color Temp	REF No
3000K	907107
4000K	907026
6000K	907108

