

LED HIGHBAY TUBE



LED HIGHBAY TUBE 50W PREMIUM WITH SOSEN DRIVER | DIMMABLE



- Workshop
- Factory
- Warehouse
- · Highway toll stations
- Gas stations
- Supermarkets
- Exhibition halls
- Stadiums
- · Other places that need light stuctures

AVAILABLE MODELS	
REF No	
905498	
905499	























LED HIGHBAY TUBE 50W PREMIUM WITH SOSEN DRIVER | DIMMABLE

ELECTRICAL DATA	
Wattage (Consumption)	50W
Valta	200 2401/
Voltage	200-240V
Constant Current	0.24A
Constant Current	0.24//
Power Factor	≥0.95

PHOTOMETRICAL DATA	
Temperature (Kelvin)	4000K or 6000K
Light color	Neutral white or cool white
Luminous efficiency	150 lm/W
Lumen	7500
Beam angle	90°
Color Rendering Index (CRI)	> 0,80
Operating Temperature	-20 °C to +50 °C
Storage Temperature	-30 °C to +60 °C
Humidity Operating	10-80% RH
Humidity Storage	10-90% RH

CAPABILITIES	
Dimmable	Yes (with 1-10V dimmable driver)

LIFESPAN & WARRANTY	
Lifespan	50.000 hrs
Warranty	5 years

DIMENTIONS & PACKAGING	
Dimensions	276x125x90 mm
Inner box	1 piece
Outer box	6 pieces

ADDITIONAL INFORMATION	
Driver	Sosen
LED Chip	SMD2835
IP Rating	IP65
Certificates	CE & ROHS

AVAILABLE MODELS	
Color Temp	REF No
4000K	905498
6000K	905499






















LED HIGHBAY TUBE 50W PREMIUM WITH SOSEN DRIVER | DIMMABLE





CAUTIONS:

- · This product must be installed by professionals.
- If there is any damage on the power line or shell, it should be taken as defective product and should not be used.
- High voltage, non-professionals are not allowed to install, disassemble the products or connect wires.

NOTES:

- · Please always use the light out of its package.
- Before starting use of the light, please check if the light was damaged during transportation. If any

damage shown, please DO not install or use it.

- Any maintenance should be performed by trained professionals only.
- Keep packaging material away from the reach of children and pets. Risk of suffocation!
- Caution. The packaging contains small parts that may be swallowed by children.
- Never leave children unattended in the vicinity of the lights and do not allow them to play with electrical

devices.

• Try to avoid looking directly in the LED beam-especially for extended periods of time. Do not shine the

LED light in another person's eyes.

- · Never cover the lights by other objects.
- Never allow the light to come into contact with open flames or external heat sources.

10.The products need to re-repair inspection or special treatment of retirement after service time

11.Non-professioonals are not allowed to disassemble and maintain the products.We have the right not to





LED HIGHBAY TUBE 100W PREMIUM WITH SOSEN DRIVER | DIMMABLE



- Workshop
- Factory
- Warehouse
- · Highway toll stations
- · Gas stations
- Supermarkets
- · Exhibition halls
- Stadiums
- Other places that need light stuctures

AVAILABLE MODELS	
Color Temp	REF No
4000K	905501
6000K	905502





















LED HIGHBAY TUBE 100W PREMIUM WITH SOSEN DRIVER | DIMMABLE

ELECTRICAL DATA	
Wattage (Consumption)	100W
Voltage	200-240V
Constant Current	0.24A
Power Factor	≥0.95

PHOTOMETRICAL DATA	
Temperature (Kelvin)	4000K or 6000K
Light color	Neutral white or cool white
Luminous efficiency	150 lm/W
Lumen	15000
Beam angle	90°
Color Rendering Index (CRI)	> 0,80
Operating Temperature	-20 °C to +50 °C
Storage Temperature	-30 °C to +60 °C
Humidity Operating	10-80% RH
Humidity Storage	10-90% RH

CAPABILITIES	
Dimmable	Yes (with 1-10V dimmable driver)

LIFESPAN & WARRANTY	
50.000 hrs	
5 years	

DIMENTIONS & PACKAGING	
Dimensions 531x125x90 mm	
Inner box	1 piece
Outer box	4 pieces

ADDITIONAL INFORMATION	
Driver	Sosen
LED Chip	SMD2835
IP Rating	IP65
Certificates	CE & ROHS

AVAILABLE MODELS	
Color Temp	REF No
4000K	905501
6000K	905502

K ZI	
ĽУ	
531x125	




















LED HIGHBAY TUBE 100W PREMIUM WITH SOSEN DRIVER | DIMMABLE



CAUTIONS:

- · This product must be installed by professionals.
- If there is any damage on the power line or shell, it should be taken as defective product and should not be used.
- High voltage, non-professionals are not allowed to install, disassemble the products or connect wires.

NOTES:

- · Please always use the light out of its package.
- Before starting use of the light, please check if the light was damaged during transportation. If any

damage shown,please DO not install or use it.

- Any maintenance should be performed by trained professionals only.
- Keep packaging material away from the reach of children and pets. Risk of suffocation!
- Caution. The packaging contains small parts that may be swallowed by children.
- Never leave children unattended in the vicinity of the lights and do not allow them to play with electrical

devices.

• Try to avoid looking directly in the LED beam-especially for extended periods of time. Do not shine the

LED light in another person's eyes.

- · Never cover the lights by other objects.
- Never allow the light to come into contact with open flames or external heat sources.

10.The products need to re-repair inspection or special treatment of retirement after service time

11.Non-professioonals are not allowed to disassemble and maintain the products.We have the right not to





LED HIGHBAY TUBE 150W PREMIUM WITH SOSEN DRIVER | DIMMABLE



- Workshop
- Factory
- Warehouse
- · Highway toll stations
- Gas stations
- Supermarkets
- Exhibition halls
- Stadiums
- · Other places that need light stuctures

AVAILABLE MODELS	
Color Temp	REF No
4000K	905503
6000K	905504
buuuk	905504























LED HIGHBAY TUBE 150W PREMIUM WITH SOSEN DRIVER | DIMMABLE

ELECTRICAL DATA	
Wattage (Consumption)	150W
Voltage	200-240V
Constant Current	0.24A
Power Factor	≥0.95

PHOTOMETRICAL DATA	
Temperature (Kelvin)	4000K or 6000K
Light color	Neutral white or cool white
Luminous efficiency	150 lm/W
Lumen	22500
Beam angle	90°
Color Rendering Index (CRI)	> 0,80
Operating Temperature	-20 °C to +50 °C
Storage Temperature	-30 °C to +60 °C
Humidity Operating	10-80% RH

CAPABILITIES	
Dimmable	Yes (with 1-10V dimmable driver)

Humidity Storage

10-90% RH

Lifespan	50.000 hrs
Warranty	5 years

DIMENTIONS & PACKAGING		
Dimensions 785x125x90 m		785x125x90 mm
	Inner box	1 piece
	Outer box	4 pieces

ADDITIONAL INFORMATION	
Driver	Sosen
LED Chip	SMD2835
IP Rating	IP65
Certificates	CE & ROHS

AVAILABLE MODELS	
Color Temp	REF No
4000K	905503
6000K	905504

K 7	
ע א	
785x125	
	,




















LED HIGHBAY TUBE 150W PREMIUM WITH SOSEN DRIVER | DIMMABLE



CAUTIONS:

- This product must be installed by professionals.
- If there is any damage on the power line or shell, it should be taken as defective product and should not be used.
- High voltage, non-professionals are not allowed to install, disassemble the products or connect wires.

NOTES:

- · Please always use the light out of its package.
- Before starting use of the light, please check if the light was damaged during transportation. If any

damage shown, please DO not install or use it.

- Any maintenance should be performed by trained professionals only.
- Keep packaging material away from the reach of children and pets. Risk of suffocation!
- Caution. The packaging contains small parts that may be swallowed by children.
- Never leave children unattended in the vicinity of the lights and do not allow them to play with electrical

devices.

• Try to avoid looking directly in the LED beam-especially for extended periods of time. Do not shine the

LED light in another person's eyes.

- Never cover the lights by other objects.
- Never allow the light to come into contact with open flames or external heat sources

10.The products need to re-repair inspection or special treatment of retirement after service time

11.Non-professioonals are not allowed to disassemble and maintain the products.We have the right not to







LED HIGHBAY TUBE 200W PREMIUM WITH SOSEN DRIVER | DIMMABLE



- Workshop
- Factory
- Warehouse
- · Highway toll stations
- Gas stations
- Supermarkets
- Exhibition halls
- Stadiums
- Other places that need light stuctures

AVAILABLE MODELS	
Color Temp	REF No
4000K	905505
6000K	905506























LED HIGHBAY TUBE 200W PREMIUM WITH SOSEN DRIVER | DIMMABLE

ELECTRICAL DATA	
Wattage (Consumption)	200W
Voltage	200-240V
Constant Current	0.24A
Power Factor	≥0.95

PHOTOMETRICAL DATA	
Temperature (Kelvin)	4000K or 6000K
Light color	Neutral white or cool white
Luminous efficiency	150 lm/W
Lumen	30000
Beam angle	90°
Color Rendering Index (CRI)	> 0,80
Operating Temperature	-20 °C to +50 °C
Storage Temperature	-30 °C to +60 °C
Humidity Operating	10-80% RH
Humidity Storage	10-90% RH

CAPABILITIES	
Dimmable	Yes (with 1-10V dimmable driver)

LIFESPAN & WARRANTY	
Lifespan	50.000 hrs
Warranty	5 years

DIMENTIONS & PACKAGING	
Dimensions	1040x125x90 mm
Inner box	1 piece
Outer box	4 pieces

ADDITIONAL INFORMATION	
Driver	Sosen
LED Chip	SMD2835
IP Rating	IP65
Certificates	CE & ROHS

AVAILABLE MODELS	
Color Temp	REF No
4000K	905505
6000K	905506






















LED HIGHBAY TUBE 200W PREMIUM WITH SOSEN DRIVER | DIMMABLE



CAUTIONS:

- This product must be installed by professionals.
- If there is any damage on the power line or shell, it should be taken as defective product and should not be used.
- $\ \cdot \ High \ voltage, non-professionals \ are \ not \ allowed \ to \ install, \ disassemble \ the \ products \ or \ connect \ wires.$

NOTES:

- · Please always use the light out of its package.
- Before starting use of the light, please check if the light was damaged during transportation. If any

damage shown, please DO not install or use it.

- Any maintenance should be performed by trained professionals only.
- Keep packaging material away from the reach of children and pets. Risk of suffocation!
- · Caution. The packaging contains small parts that may be swallowed by children.
- Never leave children unattended in the vicinity of the lights and do not allow them to play with electrical

devices.

• Try to avoid looking directly in the LED beam-especially for extended periods of time. Do not shine the

LED light in another person's eyes.

- · Never cover the lights by other objects.
- Never allow the light to come into contact with open flames or external heat sources.

 $10. The \ products \ need \ to \ re-repair \ inspection \ or \ special \ treatment \ of \ retirement \ after \ service \ time$

11.Non-professioonals are not allowed to disassemble and maintain the products.We have the right not to







LED HIGHBAY TUBE 250W PREMIUM WITH SOSEN DRIVER | DIMMABLE



- Workshop
- Factory
- Warehouse
- · Highway toll stations
- · Gas stations
- Supermarkets
- · Exhibition halls
- Stadiums
- · Other places that need light stuctures

AVAILABLE MODELS	
REF No	
905507	
905508	





















LED HIGHBAY TUBE 250W PREMIUM WITH SOSEN DRIVER | DIMMABLE

ELECTRICAL DATA	
Wattage (Consumption)	250W
Voltage	200-240V
Constant Current	0.24A
Power Factor	≥0.95

Wattage (Consumption)	250W
Voltage	200-240V
Constant Current	0.24A
Power Factor	≥0.95

PHOTOMETRICAL DATA	
	1000/ 5000/
Temperature (Kelvin)	4000K or 6000K
Light color	Neutral white or cool white
Luminous efficiency	150 lm/W
Lumen	37500
Beam angle	90°
Color Rendering Index (CRI)	> 0,80
Operating Temperature	-20 °C to +50 °C
Storage Temperature	-30 °C to +60 °C
Humidity Operating	10-80% RH
Humidity Storage	10-90% RH

CAPABILITIES	
Dimmable	Yes (with 1-10V dimmable driver)

Lifespan	50.000 hrs	
Warranty	5 years	
DIMENTIO	ONS & PACKAGING	
Dimensions	1293x125x90 mm	
Inner box	1 piece	
Outer box	4 pieces	

LIFESPAN & WARRANTY

ADDITIONAL INFORMATION		
Driver	Sosen	
LED Chip	SMD2835	
IP Rating	IP65	
Certificates	CE & ROHS	

AVAILABLE MODELS		
Color Temp	REF No	
4000K	905507	
6000K	905508	

	4
K 7	
עש	
1293x125	




















LED HIGHBAY TUBE 250W PREMIUM WITH SOSEN DRIVER | DIMMABLE



CAUTIONS:

- This product must be installed by professionals.
- If there is any damage on the power line or shell, it should be taken as defective product and should not be used.
- High voltage, non-professionals are not allowed to install, disassemble the products or connect wires.

NOTES:

- · Please always use the light out of its package.
- Before starting use of the light, please check if the light was damaged during transportation. If any

damage shown, please DO not install or use it.

- Any maintenance should be performed by trained professionals only.
- Keep packaging material away from the reach of children and pets. Risk of suffocation!
- · Caution. The packaging contains small parts that may be swallowed by children.
- Never leave children unattended in the vicinity of the lights and do not allow them to play with electrical

devices.

• Try to avoid looking directly in the LED beam-especially for extended periods of time. Do not shine the

LED light in another person's eyes.

- · Never cover the lights by other objects.
- Never allow the light to come into contact with open flames or external heat sources.

10.The products need to re-repair inspection or special treatment of retirement after service time

 $11. \mbox{Non-professioonals}$ are not allowed to disassemble and maintain the products. We have the right not to



