

DATA SHEET




LED PANEL

120X30 IP65 4000K PREMIUM 40W | NO PLUG



AVAILABLE MODELS

Color Temp	REF No
4000K	905650



DATA SHEET



LED PANEL

120X30 IP65 4000K PREMIUM 40W | NO PLUG

ELECTRICAL DATA	
Wattage (Consumption)	40W
Voltage	200-240V
Constant Current	0.90 A
Power Factor	≥0,95

PHOTOMETRICAL DATA	
Temperature (Kelvin)	4000K
Light color	Neutral white
Luminous efficiency	85 lm/W
Lumen	3400
Beam angle	120°
Color Rendering Index (CRI)	≥0,80
Operating Temperature	-20 °C to +40 °C
Storage Temperature	-30 °C to +60 °C
Working Humidity	10-80% RH
Humidity Storage	10-90% RH

CAPABILITIES	
Housing material	Aluminium
Housing color	White
Flicker-free	No
Dimmable	Yes (with dimmable driver)

LIFESPAN & WARRANTY	
Lifespan	30.000 hrs
Warranty	3 years

DIMENSIONS & PACKAGING	
Product Dimensions	1195x295x12 mm
Inner box	2 pieces
Outer box	6 pieces

ADDITIONAL INFORMATION	
IP Rating	IP65
LED Chip type	SMD4014
Luminaires Class	Class III
Certificates	CE & ROHS

AVAILABLE MODELS	
Color Temp	REF No
4000K	905650

1195x295

40W

85 lm/W

3 years

4000K

IP65

CE

A++
A+
A
B
C
D
E

} LED